

Introducing the all new

Napco Commercial Firewolf Series:

Robust, flexible 24V commercial fire systems supporting up to 255 zones/points using all-new fire devices in hardwire, wireless, conventional & addressable technologies



24V Analog Addressable, Wireless and Conventional Fire, 255, 128 or 32 point kits

GEM-C Firewolf Series 24V Commercial Intelligent Analog Addressable Fire Panels, NFPA72-compliant, 96 outputs, 4 onboard NACs (6.5A total), expandable to 24, built in Sync/Strobe/Horn Module (System Sensor & Wheelock) and dual line DACT plus optional TCP/IP reporting. Powerful battery capacity up to 32Ah total. More addressable devices than any in its class; mile-long loop lengths and more device load each. Cost-effective retrofits - supports conventional legacy devices & existing wiring (all types/gauges). Comprehensive local and remote programming & diagnostics. **Printable AHJ reports of analog device sensitivity settings with current readings (uploadable)**

- ✓ More zones/points – up to 255
- ✓ More power – 7 amps
- ✓ More NACs - 4 on board (expandable to 24)
- ✓ Built in strobe/horn sync
- ✓ More standby power
- ✓ 32 Amp hour battery capacity
- ✓ Regulated 24V output

Code-compliant Integrated Security System Option with Pre-Isolated Circuits & Power

NAC Extender provides nearly 7A and 4 onboard NACs with up to 2A ea; up to 24V 16Ah total battery capacity. Easily distributes synched bell and strobe outputs with built in module. Monitors AC, battery trouble, tamper and ground fault on Napco bus or provides universal FACP support.

Regulated Auxiliary Power Supply Commercial fire, 12V regulated 2A model

Firewolf Advanced Analog Addressable Commercial Fire Devices support auto-drift compensation and maintenance alert function

Gemini-C New UL Commercial Wireless Line with supervised tamper & automatic, continuously supervised signal strength (requires no manual test activation).

Firewolf Menu-Driven Custom Alpha Keypads Same familiar Napco ez-programming and usage. (Keyswitch support, too.)

Compliances - NFPA 72, UL Commercial Fire, UL864 9th Ed., UL985, CSFM and NYC Fire Department Certifications.



Napco Commercial™ Firewolf-Series Components for 32 to 255 Point 24V Commercial Fire Systems:

SYSTEM

- Main Control board supports up to two (2) Addressable Fire SLCs (addressable Signaling Line Circuit controllers). (*Note: Only 1 SLC is accommodated within the Medium panel enclosure.**)
- Fire 4-wire bus for keypads and non-SLC (conventional) devices, including 12V devices
- Power Supply includes either 4A or 7A @ 24V
- RS-232 Printer Module for optional onsite parallel printer
- Supports up to 7 fire keypads, GEMC-FK1, mounted anywhere on the bus. (As few as one keypad required on system for equipment savings.)
 - Easy-to-use Gemini-style menu-driven operation with backlit custom alphanumeric display and functionality for Reset, Acknowledge, Silence (with disable).
 - Full Keyswitch Support
- Synch module built in on each NAC (System Sensor & Wheelock protocols)
- Dual Phone Line built in
 - 2 On board serial ports - one for internet reporting; one for high-speed local downloading
- TCP/IP Internet reporting module
- Regulated Auxiliary Power Supply - Commercial fire, 12V regulated 2A
- Addressable SLC Loop Isolator (*optional use* - for some fire applications requiring increased circuit integrity, e.g., meets Class A, Style 7 loop requirements.
- **Choice of two enclosures** - Between the studs enclosures, recess or surface mount -
 - Larger version supports up to 32 AH at 24V. Dimensions: 24" x 14.25" x 5.2" (H x W x D) without cover. Removable battery shelves, accommodate pairs of 7Ah, 7.5Ah and 8Ah batteries, etc.
 - Medium Enclosure - supports 16 AH at 24V. Dimensions: 16" x 14.25" x 5.2" (H x W x D) without cover. (**Note: Only 1 SLC is accommodated.*) 16Ah battery backup capacity.

INPUTS

Up to 255 Zones. Zones can come from any of the following initiating devices:

- Addressable SLC Loop - supports up to (2) 126 point loops
- Commercial RF Receiver -
- Supports Commercial Wireless Fire devices
 - Wireless Smoke Detector Model GEMC-WL-SMK
 - Wireless Heat Detector Model GEMC-WL-HEAT
 - Wireless contact transmitter (for waterflow, tamper, pull stations, etc.) Model GEMC-WL-WD2.
- Conventional 1- to 4-zone EZM Expansion modules on the 4-wire fire bus or SLC loops
- Conventional 2-wire or 4-wire smoke detector input module
- SLC Fire Devices Supported:
 - Analog Smoke Detector
 - Analog Heat Detector
 - Duct Detector
 - Pull Station
 - Conventional Zone Module
 - Short Circuit Isolator

OUTPUTS

Up to 96 outputs

- Four on board Class B or 2 Class A NAC circuits, 2 amps each, total 6.5 amps at 24V
- Built in Wheelock and System Sensor NAC sync/strobe/horn protocol allows initial silence of audible appliances while maintaining visual notification, *without the use of additional modules.*
- Addressable SLC Fire Devices: Supervised relay, unsupervised relay
- Fire 4-wire bus devices: 8 zone form C relay (GEMC-RM3008), 8 open collector output (GEMC-OUT8)

Advantages

- **Easy Wire Compatibility** - Addressable SLC controller supports shielded, unshielded, twisted and untwisted wire - ideal for retrofits
- **Longer SLC loop lengths, support more device loads each, too** (see below for distance at maximum device load in alarm/standby each):
 - 10,000 ft. #14AWG • 6,200 ft. #16AWG • 4,000 ft. #18AWG
- **Support for Legacy and Existing Notification Appliances** - One NAC output configurable for 12V for easy retrofit compatibility
- UL Regulated NAC outputs
- **Automatic drift compensation** for SLC smoke detectors
- Keypads mount anywhere on the bus and have flash-able firmware - for updates via Quickloader command (# GEMC-FK1, shown above)
- **Programmable obscuration level** by smoke detector device
- **Smoke Obscuration Report generated remotely or locally or in any of 3 ways** - Quickloader device sensitivity report allows the printout of a report for the AHJ listing the current status of all smoke detectors in the system including the programmed obscuration level and the actual sensitivity reading for each device. This report can be generated remotely (uploaded) or locally through notebook PC or use optional onsite printer.
- **Full line of UL Commercial Devices for more flexibility & labor-savings** Example, Use Gemini Commercial Wireless 2-input module (GEMC-WL-WD2) to convert any UL listed fire device into a UL wireless device, ideal for sprinkler supervisories or for use with pull stations (mounts on top of wall/conduit or in deep single-gang box (plastic).
- **Separate 7Amp 4-NAC Extender (GEM-NAC7)** 4 onboard NACs with up to 2A ea., expandable for up to 24 per system. Up to 28Ah total battery capacity. Regulated 24V Aux. power. Monitors AC, battery trouble, tamper and ground fault on Napco bus - *Also Provides Universal FACP support for easy standardization in upgrades*




(Shown above)
32-Point GEM-C Firewolf™ 24V Commercial Fire System

Agencies

NFPA 72, UL Commercial Fire, UL864 9th Ed., UL985, CSFM and NYC Fire Department Certifications.

FIREWOLF SYSTEM COMPONENTS



NAPCO COMMERCIAL FIREWOLF SERIES SYSTEM ORDERING INFO.

Napco Commercial Fire Kits	
GEMC-FW-255KT	255 Point GEM-C Firewolf™ 24V Commercial Fire System Kit <ul style="list-style-type: none"> • 24V Panel, 255 Points via commercial addressable, wireless or conventional fire devices, 4 on board NACs providing up to 6.5A notification power • 7 Amp, 24V Power Supply • Built in horn/strobe synch. module on each NAC • Built in dual line communicator; dual onboard serial ports • Quickloader up/downloading including remote smoke obscuration reporting • Locking, Large Red Enclosure, 16 x 25" reversible door, with 14.25" x 25" base. Houses up to 32Ah battery backup. • Menu-driven LCD Fire Keypad mounts anywhere on bus. (Also, full keyswitch support)
GEMC-FW-128KT	128 Point GEM-C Firewolf™ 24V Commercial Fire System Kit As above, but with <ul style="list-style-type: none"> • 24V Panel, 128 Points via commercial addressable, wireless or conventional fire devices, 4 on board NACs providing up to 6.5A notification power
GEMC-FW-32KT	32 Point GEM-C Firewolf™ 24V Commercial Fire System Kit Similar to above, but with <ul style="list-style-type: none"> • 24V Panel, 32 Points via commercial addressable, wireless or conventional fire devices, 2 on board NACs providing up to 4A notification power • Locking, Medium Red Enclosure, 16 x 17" door, with 14.25" x 16" base. Houses up to 16Ah battery backup.
GEMC-FW32CONVKT	32 Point GEM-C Conventional Commercial Fire System Kit, ideal for sprinkler/waterflow apps. 24V Panel, 32 Points via commercial addressable, wireless or conventional fire devices, 4 on board NACs providing up to 6.5A notification power <ul style="list-style-type: none"> • Locking, Medium Red Enclosure, 16 x 17" door, with 14.25" x 16" base. Houses up to 16Ah battery backup. • 4 Amp, 24V Power Supply • Conventional 8-zone 2-wire fire input module, for conventional 2-wire smokes or any conventional fire detection device (GEMC-F8ZCPIM) • Built in horn/strobe synch. module on each NAC • Built in dual line communicator; dual onboard serial ports • Quickloader up/downloading including remote smoke obscuration reporting (for addressable detectors) • Menu-driven LCD Fire Keypad mounts anywhere on bus (GEMC-FK1)
Conventional Fire System Peripherals	
GEMC-FK1	LCD Fire Red Keypad (Menu-driven operation, functionality for Reset, Acknowledge, Silence (with disable).
GEMC-F8ZCPIM	Conventional 8-zone 2-wire fire input module. Plugs into motherboard, for conventional 2-wire smoke detectors or any conventional fire detection device.
GEMC-EZM8	8-point Expansion Module
GEMC-NL-MOD	Internet Reporting Module
Wireless Firewolf Peripherals	
GEMC-WL-SMK	Gemini Commercial Wireless Smoke , Photoelectric (complete).
GEMC-WL-HEAT	Gemini Commercial Wireless Heat , 135° F
GEMC-WL-WD	Gemini Comm'l Wireless slim profile 1-input wireless module
GEMC-WL-WD2	Gemini Comm'l Wireless 2-input module converts any UL listed device into a UL wireless device (ex., pull stations or sprinkler supervisories.)
GEMC-REVC	Gemini Commercial Wireless 255 point RF Receiver (up to 4 per system, max.)
Addressable Firewolf Peripherals	
GEMC-FW-SLC	Addressable SLC Fire Module , supports up to 128 addressable SLC fire devices, below. Up to 2 connect to Panel.
FWC-FSLC-SMK	Addressable Analog SLC Smoke , photoelectric, head**
FWC-FSLC-HEAT	Addressable Analog SLC Heat , 135°F, head**
FWC-FSLC-DUCT	Addressable SLC Duct smoke detector, photoelectric
FWC-FSLC-DUCTRA	Remote Indicator Plate with LED indicator & key reset.
FWC-FSLC-EZM2	Addressable SLC 2-zone conventional expansion module. Uses one address on SLC loop, but yields 2 indep. contact monitoring circuits, for pull stations, water flow and other dry contact alarm initiating devices.
FWC-FSLC-EZM1	Addressable SLC 1-input conventional module, similar to usage above.
FWC-FSLC-CZM	Addressable SLC single module , for monitoring of dry contacts, ie., pull stations and conv. smokes
FWC-FSLC-RM2	Addressable SLC 2-output module (requires 1 SLC address)
FWC-FSLC-ISO	Addressable SLC Short Circuit Module (Optional: For special applications, meets Class A, Style 7 loop reqts.)
FWC-FSLC-SOM1	Addressable SLC Fire supervised output module . Application examples: elevator recall, HVAC shutdown, add'l NAC output w/ power supply
FWC-FSLC-PULL	Addressable SLC Fire Pull Station , standard hex-key reset.
FWC-FSLC-PULLK	Version of above, with key reset .
FWC-FSLC-PULL2	Dual action pull station , with hex-key reset.
FWC-FSLC-PULL2K	Dual action, with key reset.
FWC-FSLC-PROG2	Tool for address-programming SLC devices
FWC-FSLC-SMK6B	** Smoke/Heat 6" Base , required for FWC-FSLC- SMK and -HEAT devices
Output Options	
GEMC-NAC75	Remote 4-output NAC Extender , for 6.5A ttl, or 2A, max. on any 1 output. Red 14 x 16" can, connects to 120VAC, supports 24V 28Ah standby batts. Supervised, fire bus connection. System Sensor and Wheelock NAC synch. (5/system, for 20 add'l NAC circuits ttl.)
GEMC-12V2APS-CF	12VDC Power Supply for Fire Bus , remote supervised. Direct 120VAC connection, supports 2ea. 12V, 7Ah to 18Ah standby batts.
GEMC-FPRINT	Parallel Printer Module
GEMC-RM3008	8 Form C Relay Output Module
GEMC-RS232	RS232 Adapter for serial output from Panel
GEMC-OUT8	PGM Output Module , 8 open collector PGM outputs



NAPCO Security Technologies, Inc.
 www.napcosecurity.com
 1-800-645-9445 • 631-842-9400
 Amityville, NY USA