

Trilogy T3 DL3000

B. Digital Locksets shall meet or exceed ANSI A156.2 Series 4000, Grade 1 standard for cylindrical lever locks. Locks shall be FCC Certified and listed UL10C Positive Pressure for "A" 3hour fire rated openings. Trim design shall be ADA compliant, chosen from manufacturers standard lever designs. Locks shall have a deadlocking latch bolt and be of the electronic battery digital type, with up to 300 available codes including, Master, Manager, Supervisor, and basic user codes. Locks to have Real Time Clock allowing 150 scheduled events and holiday scheduling. Locks to provide user lockout mode and 4 built-in "Quick Schedules" of the most common routines. All locks to be UL listed, fire rated 3 hours. Furnish manufacturer's power pack with each lock; Locks shall have key override or the optional 2-wire remote release capability using the built in Form C relay output. to include batteries. Keypads to be all metal, 12 buttons. All functions programmed through keypad or PC, with intuitive Alarm Lock DL-WINDOWS Software. All locks to have standard key bypass and 2-wire remote release capability, and built in Form C relay output. All locks to fit standard ANSI A115 Series prep, modified by adding additional through-bolt holes. Locks shall be non-handed and provided with strikes as required. Provided with standard 6 pin cylinder, optional 6 or 7 pin IC type core is also available (See keying Requirements) Locks at exterior openings or wet areas, shall have "WP" waterproof protection option. Lock function as shown in hardware sets. Scheduled product is from Alarm Lock* Trilogy T3 DL3000 series. No approved equals.